

Thank you for selecting one of the finest speakers available. To ensure optimum performance of your new Naylor Speaker, please follow the guidelines listed below:

- \* In order to enact the warranty, complete and mail warranty form to Naylor Engineering, within 15 days from date of purchase.
- \* Before mounting speakers, make sure the cabinet baffle (the surface the speaker mounts to) is securely attached to cabinet. A loose baffle will cause poor projection, sloppy low end response and unwanted noises from vibration.
- \* Use lock washers with speaker mounting screws. Gradually tighten screws, ½ turn at a time, alternating between screws directly opposite one another. Do not over tighten mounting screws!
- \* Total speaker impedance (ohms) should match amplifier impedance (ohms). A mismatch could seriously damage your amplifier.
- \* Do not exceed speaker power rating. Amplifier power rating (watts RMS) should be equal to or less than speaker wattage rating.
- \* If you do not understand any of the above, have speakers installed by a qualified technician.
- \* IMPORTANT – New speakers require a short break-in period before reaching optimum tone and performance. Approximately 20-30 minutes of playing at a moderate volume level is sufficient.

For more information on Naylor Speakers, Amplifiers, Cabinets and Accessories visit the Naylor web site at [WWW.naylorengineering.com](http://WWW.naylorengineering.com)